

Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street,
Nei Hu District Taipei 114, Taiwan R.O.C.
TEL: +886-2-8751-1111
FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
http://www.protech.com.tw

Protech Japan Co., Ltd.

OSK Bldg, 6F, 6-25-14, Minami-ohi
Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411
FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
http://www.protech-j.com

Protech Technologies Inc.

950 Fee Ana St, Suite B
Placentia, CA 92870
TEL: +1-714- 996-7200
FAX: +1-714- 996-7300
Sales: sales@protech-usa.net
http://www.protech-usa.net

PROX SYSTEMS Germany GmbH

Weststrasse 20a, 40721 Hilden
Düsseldorf, Germany
TEL: +49 (0) 2103-41898-18
FAX: +49 (0) 2103-41898-10
E-mail: steffi.surau@prox-systems.com

Accessory Display & Printer

BarcodesInc has more than a decade of experience offering complete POS solutions to our retail and hospitality customers. Whether you need to set up a complete POS system





MP-1060


Fast printing speed up to 200mm per second
Easy drop in paper loading
Small footprint & Ergonomic design

Various interface

- USB/Serial Combo (Standard)
- Ethernet (Optional)
- Bluetooth (Optional)
- Wifi (Optional)


Value-added options available

- Melody Box
- Splash proof cover
- Cable Cover
- Wall mount bracket
- 2" Paper Selecting Card



MP-4003

Item	Sub-Item	Spec criteria Description
Display method	-	VFD display
Display pattern	-	20x2 Dot Matrix
Character	Format	5x7+Dp,com,descriptor
	Type	95 Alphanumeric, 12 sets of 12 characters each
	Size	5.25 mm(W) x 9.03 mm(H)
Dot Size (X * Y)	-	0.85 mm(X) x 1.05 mm(Y)
Brightness	-	350 ~700 cd/m ²
Number of Character	-	40 (20 columns x 2 lines)
Interface	RS232C	Baud Rate : 9600 / 19200 Bps
Command Mode	-	P4000, EPSON POS D101 (default), AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support	-	USA, France, Germany, UK, Denmark I, Sweden, Italy, Spain, Japan, Norway, Denmark II, lavonic, Russia
Dimensions	Panel	217.3 mm (W)× 44.6 mm (D) × 63.4. mm (H)
	Adjustable pole	Max Length= 280.5mm ; Min Length=155.5mm
	Base	145.2 mm (W)× 90.0 mm (D) × 32.0 mm (H)
Weight(kg)	-	850 g
Power	Source	5/12 VDC
	Consumption	2.64 Watts
Safety	-	FCC Class A B, CE
Reliability	MTBF	30,000 hours
Environmental	Operating temperature	-20 to 70°C (85%RH max)
	Storage temperature	-40 to 80°C (90%RH max)
	Operating humidity	85%max, non-condensing
	Storage humidity	90%max, non-condensing
Emulation	-	OPOS



Spec & Features

- 200mm High speed printing
- Built-in Traditional Chinese and Japanese Kanji character
- Built-in multi-language codepage
- Support digital LOGO printing saved in FLASH ROM
- Modularized design of printer head.
- Dual interface for USB/Serial Port supported
- Auto paper cutter for full cut and partial cut available
- Paper-near-end detector sensor and LED/Buzzer warning indicator
- EPSON Command and other Emulation
- Barcode Multiple printer function capable
- Easy to set and high volume capacity of paper
- Spectacular value-add accessories
- Support Windows system

Applications



Digital Receipts



Analytics



Information Display



Mobile POS

Features

- High quality vacuum fluorescent customer display - 20 Cols x 2 Lines by 5 x7 font
- High brightness and speedy display response - Easy to read
- Wide viewing angel- Vertical range 45°; Horizontal range 125°
- Multiple language supported – Built-in 12 International fonts
- Wide temperature- Range -40°C to +80°C
- Adjustable pole –Easy to set up
- ESC/POS and 10 other commands supported
- OPOS driver supported